

## Product Information

POLI-FLEX® BLOCKOUT SOFT is a Sublimation-resistant, multi-layer polyurethane film with a high opacity and a pleasantly soft touch. Even high temperatures will not cause any sublimation inks to bleed through the garment.

POLI-FLEX® BLOCKOUT SOFT is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic.

POLI-FLEX® BLOCKOUT SOFT can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

POLI-FLEX® BLOCKOUT SOFT can be cut with all current plotters. We recommend using a standard 45° knife. After weeding the cut flex film is transferred by heat press. To avoid a sublimation-migration we recommend that the garment is not pre-heated. The PET liner should be removed warm. Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX® NYLON.

The soft, elastic transfer film offers a comfortable textile touch and convinces due to high wearing comfort. POLI-FLEX® BLOCKOUT SOFT excels due to an excellent opacity. POLI-FLEX® BLOCKOUT SOFT with a self-adhesive PET liner enables a reposition. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals.

Guarantee for a secure and long-lasting bond of POLI-FLEX® BLOCKOUT SOFT is only given when following the specified temperature and pressure conditions.

### We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Please note that restrictions may occur when using stretchable garments due to the BLOCKOUT layer. As a result, creases, cracks or crinkles can appear. This depends strongly on the composition of the textile as well as the size and kind of lettering used.

## Technical Data

|                        |                         |
|------------------------|-------------------------|
| <b>Transfer Film:</b>  | Polyurethane, cast      |
| <b>Adhesive:</b>       | Co-polyester-hotmelt    |
| <b>Thickness [mm]:</b> | 0,125      +/- 5 %      |
| <b>Liner:</b>          | PET-film, self-adhesive |

## Transfer Conditions

|                     |                                 |
|---------------------|---------------------------------|
| <b>Temperature:</b> | 130 °C                          |
| <b>Pressure:</b>    | 2,5 - 3,0 bar [medium pressure] |
| <b>Time:</b>        | 5 sec.                          |

## Wash Resistance

|                         |  |
|-------------------------|--|
| <b>Wash resistance:</b> | 60 °C<br>Suitable for dry-cleaning (Perchloroethylene / Tetrachloroethylene). Wash textile inside out. |
|-------------------------|--|

## Dimensions

500 mm x 10 m, 500 mm x 25 m, 1.000 mm x 25 m\*, 1.524 mm x 25 m\*

\* Non-standard dimension. Converted after order entry. Extended delivery times may occur.

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.